

Bag filter

AFE

For cacao

1. Introduction

For a wide number of filtration applications bag filters are a simple, easy to use and economical choice. Within the edible oil industry bag filters are commonly used during several process steps.

These AFE bag filter housings are excellent for use in the safety filtration edible oil at the end of crude oil or bleaching steps, for example. But they are also suitable for polishing filtration of edible oil. The AFE bag filter housings are available for size 1 and size 2 filter bags and manufactured from stainless steel.

The maximum temperature for these housings is 120 °C.

The design temperature in combination with the PED category makes these housings an economical filter solution for edible oil applications.



2. Features

- Easy to use, good interior sealing and accessibility.
- Cover closing with hinged eye bolts and eye nuts (galvanised steel).
- Stainless steel bolts and nuts optional.
- Flat cover with handle.
- O-ring sealing: standard Buna-N. Other materials on request.
- Strong stainless metal mesh support basket for low flow resistance and maximum utilisation of entire surface area.
- Slightly conical support basket for easy filter bag removal.
- Liquid displacement cover: no liquid runs over the side when opening the filter.
- Liquid displacer units are available to further reduce the dead volume inside the filter bags.
- Perfect sealing between unfiltered liquid and filtered liquid is achieved by a spring-loaded hold-down device onto the filter bag and support basket. The filter bag seals with a felt-covered Snap-Collar ring or plastic seal which tightly fits into the support basket.
- Height-adjustable legs.


4. Filter bags

Filtration Group supplies a wide range of filter bags in different materials, pore sizes, dimensions and models to fit in amafilter housings as well as those of other manufacturers. For detailed information about amaFlow filter bags, please see respective Data Sheets.

3. Standard specifications

Design pressure	: 0 / 10 bar(g)
Design temperature	: - 10 / 120 °C
Operating temperature	: depending on the filter media and gaskets used
PED 97/23/EC cat.	: article 3 paragraph 3
Maximum differential pressure	
design	: 4.0 bar
operating	: 2.5 bar

5. Dimensions



Nozzle specification	
N1 :	Inlet
N2 :	Outlet
N3 :	Vent (Rp ¼ - ISO7-1)

Dimensions						
Size	Diameter [mm] A	Standout [mm] B	Height [mm] C	Nozze height [mm] D	Volume [dm³]	Weight [kg]
90	219	156	max. 1020	max. 895	19	max. 21
180	219	Threaded: 156 Flanged: 210	max. 1370	max. 1245	34	max. 33

Dimensions are for reference only. Use dimensional drawing for installation purposes.
Subject to technical alteration without prior notice.

6. Ordering code

Example

AFE 180 T 2F

Filtration Group type

AFE

Size

90 = for bag size 1

180 = for bag size 2

Material

No symbol = carbon steel

T = 316Ti (1.4571)

TY = 316Ti (1.4571) with stainless steel bolts and nuts

Inlet/outlet

2 = Rp2 - ISO7-1

Size 180 only

2F = DN50 acc. EN1092/PN16

3F = DN80 acc. EN1092/PN16

ASME 150 lbs RF on request (FA)

Filtration Group BV
Postbus 35
NL - 7240 AA Lochem
Phone +31 573 297 777
info.FGNL@filtrationgroup.com
www.filtrationgroup.com
02/2017