

Filtration Group BV Postbus 35 NL - 7240 AA Lochem The Netherlands +31 573 297 777

info.FGNL@filtrationgroup.com www.filtration.group

August, 2017

Cartridge filter

AFL-1

1. Introduction

An economic and shatter resistant three piece filter housing, designed for a wide range of applications, for example food and beverage, plating, chemical processes and water.




2. Features

- Suitable for a single cartridge
- Three piece construction with cover closing by means of a nut
- Filter housing materials conform to the FDA requirements
- O-ring sealing standard EPDM. Other materials on
- request.
- Vent plug standard
- Spanner for tighten the nut included
- Drain plug on 20" housing

Optional

Mounting brackets

3. Outline drawing



Dimensions

Filter model	A [mm]	B [mm]]	C [mm
AFL1-10	126	350	58
AFL1-20	126	615	58

amafilter

LFC Lochem



4. Ordering code

Example

AFL1	10	P	1	PV
Туре	Cartridge length	Material bowl	Inlet/Outlet	Material head
	10 = 10" or 9 ¾" 20 = 20"	P = polypropylene A = styrene acrylonitrile (SAN)	¾ = ¾" BSP 1 = 1" BSP	No symbol = polypropylene with brass inserts PV = polypropylene



LFC Lochem